

**LITHIUM BATTERIES**



Cell size references:A

**ER17505M  
3.6V 3000mAh**

**lithium-thionyl chloride batteries**

**Electrical characteristics**

(Stored for one year or less)

◉ Nominal Capacity ( 2 mA to 2.0V, at 25°C)	3000 mAh
◉ Nominal voltage	3.6V
◉ Max continuous discharge current	1000mA
◉ Max. Pulse current Current value is obtaining 2.0V cell voltage when pulse is applied for 15 seconds at 50% discharge depth at 25°C	2000mA
◉ Storage temperature	20°C ~ 30°C
◉ Operating temperature	-55°C ~ 85°C
◉ Weight(approx)	30g

**WARNING:**

Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 100°C, incinerate or expose contents to water.

**Key features**

- High and stable operating voltage
- Low self-discharge rate  
Less than 1% after 1 year of storage at 20°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard
- Non-restricted for transport


**Main applications**

- TPMS
- Alarms and security system
- Memory back-up
- Tracking system
- Automotive electronics
- Professional electronics
- Computer real-time clocks


.....

**LITHIUM BATTERIES**


Typical discharge at 25°C



Voltage plateau versus Current and Temperature




Capacity versus Current and Temperature



**ER17505M**

lithium-thionyl chloride batteries



Unit: mm

Available Terminations	
-/P	Axial Pin
-/T /PT2	Radial Pin
-/PT /TP	Polarized Tab