



Maintenance-Free Rechargeable Sealed Lead-Acid Battery




# EVP12-12

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glass-mat separator and plates, the battery can use in any direction and position without leakage.

## PERFORMANCE SPECIFICATIONS


Nominal Voltage(V).....	12 volts(6cells in series)
Nominal Capacity(AH)	
20 Hour rate F.V.(1.75V/cell) (0.6A to 10.50volts) .....	12.0A.H.
5 Hour rate F.V.(1.75V/cell) (2.04A to 10.50volts).....	10.2A.H.
30 Min rate F.V.(1.30V/cell) (15.0A to 7.80volts).....	7.5A.H.
Approximate Weight .....	4200g(9.25lbs.)
Terminal	
Standard.....	Type T2
Optional.....	Type T1
Internal Resistance (Fully Charged Battery).....	<12m Ω
Maximum Discharge Current For 5 sec.(A).....	180A
Maximum Charge Current(A).....	3.6A
Ambient Temperature	
Charge.....	0°C(32°F)~40°C(104°F)
Discharge.....	-20°C(-4°F)~50°C(122°F)
Storage.....	-20°C(-4°F)~40°C(104°F)
Vibration test:	
Frequency: 16.7HZ	
Amplitude: 4mm	
Vibrate the battery horizontally or vertically for 60 minutes. The battery have no abnormality.	
Case.....	ABS
Dimension (mm/inch)	
Length           ±1.5mm.....	151/5.94
Width           ±1.5mm.....	98/3.86
Container Height ±1.5mm.....	94/3.70
Total Height   ±2mm.....	98/3.86
Application.....	Electrical Bicycle, Fishing Lights.

## EVP12-12 Battery discharge characteristics (25 °C/77 °F)




## Battery Charging Characteristics

(Typical example of the charge characteristic for the cycle use)



## Battery Life Characteristics of Cyclic Use

Testing Conditions: Discharge Current : 1C Amp (F.V. 1.60v/cell)  
 Charging Current : 0.1C Amp  
 Charging Volume : 120% OF Discharge Capacity  
 Ambient Temperature : 20 °C (68 °F)




## Charging Procedure


Application	Charging method	Charging Voltage at 20 °C (V/cell)	Temperature compensation coefficient of charging voltage (mV/°C/cell)	Max. charging current (CA)	Charging time 0.1CA, 20 °C (h)		Temp (°C)
					100% discharge	50% discharge	
For standby power source	Constant voltage & Constant current charging (with current restriction)	2.25-2.30	-3	0.3	24	20	0~40 (32-104°F)
For cycle service		2.40-2.50	-4	0.3	16	10	

\*Temperature compensation of charging voltage is not needed, when using the batteries within 5 °C to 35 °C range.

## OUTER DIMENSIONS mm(inch)




## TERMINAL TYPE mm(inch)



## Constant power discharge characteristics at 25°C/77°F

Final Voltage	Discharge time								
	5Min	10Min	15Min	30Min	45Min	1Hr	3Hr	5Hr	10Hr
10.80V	515	365	276	163	117	93.9	37.7	24.0	13.4
10.50V	597	396	290	170	122	97.0	38.7	24.5	13.7
10.20V	634	411	299	174	124	99.1	39.4	24.7	13.8
9.90V	662	421	305	178	126	100.1	39.8	24.9	13.8
9.60V	684	428	311	180	127	100.8	39.9	24.9	13.8

## TERMINAL POSITION



**B.B. BATTERY CO., LTD.** Web Site: <http://www.bb-battery.com>

USA :  
 B&B BATTERY (USA) INC.  
 6415 RANDOLPH ST. COMMERCE,  
 CA, 90040 U.S.A.  
 TEL: 1-323-278-1900 1-800-278-8599  
 FAX: 1-323-278-1268

CHINA FACTORY:  
 CHENG DONG TRIAL AREA, HUANG GANG,  
 RAOPING GUANG DONG, CHINA, 515700  
 TEL: 86-768-7601001-2  
 FAX: 86-768-7601469

UK:  
 B & B BATTERY (UK) CO., LTD.  
 TEL: 44-161-339-9458  
 FAX: 44-161-343-7030

HONG KONG:  
 NATIONAL TRADING LTD.  
 TEL: 852-2301-3800  
 FAX: 852-2739-1182

JAPAN:  
 B & B BATTERY (JAPAN) CO., LTD.  
 TEL: 81-426-256-537  
 FAX: 81-426-256-537

TAIWAN:  
 B & B BATTERY CO., LTD.  
 TEL: 886-6-5898081-3  
 FAX: 886-6-5898087

